

1-Chip DLPTM-Laserprojektoren für den Bildungs- und Unternehmensbereich

PT-FRZ60

Bedienfreundliche, einfache 1-Chip DLPTM-Laserprojektoren für scharfe Bilder in hellen Räumen mit flexibler Integration in Unterrichtsräume oder Büros



KEY FEATURES

- 1-Chip DLP-Laserprojektor, 6.200 Lumen (Mitte), WUXGA
- DLPTM-Bildtechnologie, Quartet Colour Harmonizer, Rich Colour Enhancer und Optimierung durch digitale Modulation mit Dynamic Contrast 2
- Bis zu 20.000 Stunden wartungsfreier Betrieb dank staubdichtem optischen Block und langlebigem Lasersystem
- Flexibles zweifaches Zoomobjektiv (1,46 – 2,94:1) mit V/H Lens-Shift
- Unterstützt unkomprimierte 4K/60p-Eingangssignale über HDCP 2.2-kompatible HDMI®-Eingänge oder DIGITAL LINK-Anschluss



SPECIFICATIONS

Dimensions (W x H x D)	498 x 168*5 x 492 mm (19 5/8" x 6 5/8"*5 x 19 3/8")
Power Consumption	TBD
Lens	2.0x manual zoom (throw ratio: 1.46–2.94:1), manual focus, F 2.0–3.4, f 21.5–43.0 mm
Auflösung	1920 x 1200 pixels
Operating Environment	Operating temperature: 0–40 °C (32–104 °F), operating humidity: 10–80 % (no condensation) (TBD)
Keystone Correction Range	Vertical: ±40 °, Horizontal: ±20 °. When [VERTICAL KEYSTONE] and [HORIZONTAL KEYSTONE] are used simultaneously, correction cannot be made exceeding a total of ±60 °.
Installation	Ceiling/floor, front/rear, free 360-degree installation
Cabinet Materials	Molded plastic
Applicable Software	Logo Transfer Software, Multi Monitoring & Control Software, Early Warning Software
Contrast Ratio*1	20,000:1 (Full On/Full Off, Dynamic Contrast Mode: ON)
Power Supply	AC 100–240 V, 50/60 Hz
Light Source	Laser diodes
Terminals LAN	RJ-45 x 1 for network connection, PJLink™ (Class 2) compatible, 10Base-T/100Base-TX, Art-Net compatible
DLP™ Chip Panel Size	17.0 mm (0.67 in) diagonal (16:10 aspect ratio)
DLP™ Chip Display Method	DLP™ chip x 1, DLP™ projection system
Terminals HDMI In	HDMI 19-pin x 2 (Compatible with HDCP 2.2, Deep Color, 4K/60p signal input*4), CEC supported
Terminals DIGITAL LINK	RJ-45 x 1 for network and DIGITAL LINK connections (HDBase™™ compliant), PJLink™ (Class 2) compatible, 100Base-TX, Art-Net compatible, HDCP 2.2 compatible, Deep Color compatible, 4K/60p signal input*4
Light output	6,000 lm*1/6,200 lm (Center)*2
Operation noise*1	30 dB (Quiet Mode) (TBD), 35 dB (Normal Mode) (TBD)
Projector type	1-Chip DLP™ projector
DLP™ chip Number of Pixels	2,304,000 (1920 x 1200 pixels)
Screen size [diagonal]	1.02–7.62 m (40–300 in), 16:10 aspect ratio
Center-to-corner zone ratio*1	90 %
Time until light output declines to 50 %*3	20,000 hours (NORMAL)
Note	*1 Measurement, measuring conditions, and method of notation all comply with ISO/IEC 21118: 2012 international standards. Value is average of all products when shipped. *2 Average light-output value of all shipped products measured at center of screen in NORMAL Mode. *3 Around this time, light output will have decreased by approximately 50 %. IEC62087: 2008 Broadcast contents, NORMAL Mode, Dynamic Contrast [ON], under conditions with 35 °C (95 °F), 700 m (2,297 ft) above sea level, and 0.15 mg/m3 of particulate matter. Estimated time until light output declines to 50 % varies depending on environment. *4 4K signals are converted to the projector's resolution (1920 x 1200 pixels) upon projection. Supported terminals: DIGITAL LINK/HDMI®. *5 With legs at shortest position. *6 Average value. May differ depending on the actual unit.
Weight*6	Approx. 16.6 kg (36.6 lbs) (TBD)
Terminals Computer 1 In	D-sub HD 15-pin (female) x 1 (RGB/YBPBR/YCBCR/YC)
Terminals Video In	Pin jack x 1 (composite video)
Terminals Audio In 1	Pin jack x 2 (L, R)
Terminals Serial In	D-sub 9-pin (female) x 1 for external control (RS-232C compliant)
Terminals USB	USB connector (Type A) x 1 (Output 5 V/2 A)
Terminals Audio Out	M3 x 1 (Variable)

Terminals Computer 2 In/1 Out	D-sub HD 15-pin (female) x 1 (RGB/YPBPR/YCBCR/YC)
Lens shift Vertical(From the origin point of the lens mounter)	+64 %, -44 % (manual)
Lens shift Horizontal(From the origin point of the lens mounter)	+34 %, -27 % (manual)
Terminals Audio In 2/3	M3 x 1/M3 x 1

URL: <https://business.panasonic.de/visuelle-systeme/pt-frz60-0>

CONTACT

Web: <https://business.panasonic.de/visuelle-systeme/contact-us>